

you can
Canon

i905D

Bubble Jet Printer

*The ultra versatile,
direct photo printer*



OFFICIAL PARTNER



Professional photo quality, quickly and simply

For PC-free photo printing, direct from memory cards or any compatible digital camera, the i905D gives you far greater freedom. This ultra flexible printer provides ultimate photo quality, extensive photo features and comes with creative software applications. Delivering eye-catching prints that you can present with pride.



CONNECT

Simply plug in a compatible memory card into the built-in card reader slot.
Or connect your PictBridge or Bubble Jet Direct compatible camera to the i905D.



DIRECT PHOTO PRINTING WITH PICTBRIDGE SUPPORT

Enjoy extra easy and almost instant photo development. Simply print direct from all popular memory cards as well as any compatible PictBridge or Bubble Jet Direct digital camera or camcorder. A colour LCD viewer, with an easy to use interface, lets you view, select and choose the print settings for your favourite photos before printing - for straightforward control without even using a PC.



**Conventional/
Competitors**



**Advanced MicroFine
Droplet Technology™**



Traditional ink jet printing systems may deliver droplets of irregular placement and shape. Canon's advanced MicroFine Droplet Technology™ improves the control process for droplet ejection, delivering consistent drops with exact form and placement.

OUTSTANDING PHOTO LAB QUALITY

Benefit from exceptional colour quality and depth for all your prints. A six ink printing system, high colour and 1/6 density photo inks, ensures a flawless finish. There's an ultra high 4800 x 1200 dpi¹ resolution, thanks to Canon's advanced MicroFine Droplet Technology™ and 2 pl Micro-Nozzles. Delivering natural looking results, consistently.

QUALITY

EASE

FAST BORDERLESS PRINTING, CONVENIENT FEATURES

Make use of fast, borderless printing on A4, 5" x 7" and 4" x 6" formats for ready-to-frame prints. Time-saving speed lets you print a 4" x 6" photo in only 49 seconds. A dedicated photo paper tray avoids the need to switch paper constantly. Plus you can print directly and easily onto CD-R/DVD disks, instead of using messy labels.

SINGLE INK TECHNOLOGY

With individually replaceable ink tanks for all colours, Canon's Single Ink technology ensures all ink is used - to eliminate waste and cut down on your costs.



SELECT


Select the layout and number of prints on the integrated LCD viewer with the easy to use interface.



PRINT

Press 'print' and within seconds your photo is ready, without the need for a PC

ADVANCED IMAGE
COMPOSITION FEATURE
INCLUDED IN EASY-
PHOTOPRINT



Original image



Compose your image



Enhanced results

EXTENSIVE SOFTWARE SOLUTIONS

Versatile software solutions gives you full freedom for creativity. Manipulate, manage and print your photos as you want, allowing you to display an impressive photo album on demand. Canon's special software solution disk, containing PhotoRecord and ZoomBrowser, ensures unlimited inventiveness. Other useful software tools include Easy-WebPrint & Exif Print support via Easy-PhotoPrint, for enhanced output.

WINDOWS & MAC COMPATIBLE

Put compatibility problems behind you - as the i905D printer works with all popular Windows and Macintosh operating systems, with USB connectivity.



Canon Bubble Jet i905D Specifications

Resolution	Up to 4800 x 1200 dpi ¹
Print engine	6-ink with Micro-Nozzles, advanced MicroFine Droplet Technology™, 2pl
Colour management	ICM, ColorSync, Exif Print
Mono print speed	Mono Text: Up to 8ppm (Max), 3.7ppm (Std)
Colour print speed	Text & Graphics: Up to 7ppm (Max), 2.6ppm (Std); A4 Full Page: Up to 0.7ppm (Std)
Photo print speed	4"x6" [10x15cm] print in approx. 49 seconds (Std on PR-101)
Media type	Plain Paper, Envelopes, High Resolution Paper (HR-101N), Glossy Photo Paper (GP-401), Photo Paper Pro (PR-101, PC-101S), Photo Paper Plus Glossy (PP-101), Photo Paper Plus Semi-gloss (SG-101), Matte Photo Paper (MP-101), Transparency (CF-102), T-shirt Transfer (TR-201)
Media weight	Sheet feeder: 64 to 105 g/m² and supported Canon special media up to 270 g/m²
Media input	Sheet feeder: 150 sheets (50 sheets with Photo Paper Tray installed) CD-R print kit (supplied): 1 printable CDR/DVD Photo Paper Tray (supplied): 20 sheets of photo media
Media size	Sheet feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 5"x7", 4"x 6" & custom size Photo Paper Tray: 4"x6"
Borderless printing	Photo Paper Pro (A4 & 4"x6"), Photo Paper Plus Glossy (A4, 5"x7" & 4"x6"), Photo Paper Plus Semi-gloss (A4 & 4"x6"), Glossy Photo Paper (A4 & 4"x6"), Matte Photo Paper (A4)
Ink cartridge configuration	Single Ink technology - six separate ink tanks (BCI-6BK, BCI-6C, BCI-6M, BCI-6Y, BCI-6PC, BCI-6PM)
Black ink tank life	430 pages at 5% coverage ²
Colour ink tank(s) life	540 pages (Printing ISO/JIS-SCID N5) ³ 430 pages at 5% coverage per colour ³ Cyan: 780 pages, Magenta: 580 pages, Yellow: 360 pages, Photo Cyan: 410 pages, Photo Magenta: 260 pages (Printing ISO/JIS-SCID N5) ³ , USB
PC interface & connectivity	Direct Print Port: Direct photo printing from PictBridge & Bubble Jet Direct compliant digital cameras & camcorders
Camera interface & connectivity	Compatibility: Exif 2.2 or earlier, DPOF compliant
Camera direct printing	Storage compatibility: CompactFlash™ card/Microdrive™, SmartMedia™, Memory Stick™ (excluding PRO), SD card/Multimedia card; xD-Picture card*, Memory Stick DUO*, miniSD Card* (* using recommended adapter - not supplied)
Card direct printing	Built-in 2" colour LCD display
Image viewer	Windows: PC with Windows XP, Windows 2000, Windows Millennium or Windows 98, USB interface ⁴ , CD-ROM Drive. Free hard disk space for printer driver installation: 75 MB for Windows 2000/XP, 40 MB for Windows ME/98.
Operating system requirements	

Driver features	Mac: Macintosh computer with Mac OS 8.6-9.x or Mac OS X v10.2.1 or later, USB interface. Free hard disk space for printer driver installation: 40 MB for Mac OS 8.6-9.x, 110 MB for Mac OS X v10.2.1 Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo Mac: Photo Optimizer PRO, Photo Noise Reduction, Vivid Photo
Software included	Windows: Easy-WebPrint, Easy-PhotoPrint, CD-LabelPrint, PhotoRecord, ZoomBrowser EX, Photo Viewer, Easy-PrintToolBox Mac: Easy-PhotoPrint, CD-LabelPrint
Power source	AC 220-240V 50/60Hz
Power consumption	Approx. 3W (standby), approx. 30W (printing)
Temperature range	5 - 35 C
Humidity	10 - 90% RH
Acoustic noise levels	Approx. 34dB(A) (quiet mode)
Dimensions (W x D x H)	432 x 300 x 194mm
Weight	Approx 5.6kg

¹ Ink droplets can be placed with a minimum pitch of 1/4800 inch.
² All figures are approximate and quoted for A4 media. For reference only: black calculation based on printing 1500 characters normal text in Standard Mode on plain paper with Windows XP.
³ All figures are approximate and quoted for A4 media. For reference only: calculation based on printing the ISO/JIS-SCID N5 pattern in Standard Mode on plain paper with Windows XP.
⁴ USB operation can only be guaranteed on a PC with pre-installed Windows XP, Windows 2000, Windows ME or Windows 98 (This includes Windows XP, Windows 2000 and Windows ME upgraded from pre-installed Windows 98 or later).

All specifications subject to change without notice.
 Print speeds may vary with computer system specifications and content of document printed.
 Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.
 All brand and product names are trademarks of their respective companies.

Specification CEL 1.1.1 110703

Mono print speed measured using this pattern

Colour print speed measured using this pattern

Ink coverage measured using this pattern

SUPERIOR PRINT QUALITY COMES WITH CANON INK AND MEDIA

Black Ink Tank BCI-6BK

Cyan Ink Tank BCI-6C

Photo Cyan Ink Tank BCI-6PC

Magenta Ink Tank BCI-6M

Photo Magenta Ink Tank BCI-6PM

Yellow Ink Tank BCI-6Y

you can
Canon



Canon Europa N.V.
 P.O. Box 2262, 1180 EG Amstelveen,
 The Netherlands
www.canon-europe.com

Canon Inc.
 30-2, Shimomaruko 3-Chome, Ohta-ku,
 Tokyo 146-8501, Japan
www.canon.com

English Edition 0038W511
 © Canon Europa N.V., 2003 (0903)